

GEOPHYSICAL SURVEY REPORT

Berrow Green Road, Martley

Client

Orion Heritage

on behalf of

Hayfield Homes Limited

Survey Report

13639

OASIS Ref. No.

sumogeop1-518908

WSM number

WSM80396

Date

15 September 2023



Survey Report 13639: Berrow Green Road, Martley

Survey dates	1 September 2023
Field co-ordinator	Liam Brice-Bateman BA
Field Team	Darcy Hooper MSc
Report Date	15 September 2023
CAD Illustrations	Charlotte Mawdsley BA MA
Report Author	Charlotte Mawdsley BA MA
Project Manager	Simon Haddrell BEng AMBCS PCIfA
Report approved	Dr John Gater BSc DSc(Hon) MCIfA FSA

SUMO Geophysics Ltd

Vineyard House
Upper Hook Road
Upton upon Severn
Worcestershire
WR8 0SA

T: 01684 592266

www.sumoservices.com
geophysics@sumoservices.com

TABLE OF CONTENTS

1	LIST OF FIGURES.....	3
2	LIST OF APPENDICES	3
3	SURVEY TECHNIQUE	3
4	SUMMARY OF RESULTS	3
5	INTRODUCTION.....	4
6	RESULTS.....	5
7	DATA APPRAISAL & CONFIDENCE ASSESSMENT	5
8	CONCLUSION	5
9	REFERENCES.....	7
10	ARCHIVE	7

1 LIST OF FIGURES

Figure 01	NTS	Site Location
Figure 02	1:1500	Magnetometer Survey - Greyscale Plot
Figure 03	1:1500	Magnetometer Survey - Colour Plot
Figure 04	1:1500	Magnetometer Survey - Interpretation
Figure 05	NTS	Greyscale Plots, 2009 Aerial Image, c. 1892-1914 Ordnance Survey Map and Interpretation
Figure 06	1:1500	Minimally Processed Data - Greyscale Plot
Figure 07	1:1500	XY Trace Plot (clipped at +/-15nT)

2 LIST OF APPENDICES

Appendix A	Technical Information: Magnetometer Survey Methods, Processing and Presentation
Appendix B	Technical Information: Magnetic Theory
Appendix C	OASIS Data Collection Sheet

3 SURVEY TECHNIQUE

- 3.1 Detailed magnetic survey (magnetometry) was chosen as the most efficient and effective method of locating the type of archaeological anomalies which might be expected at this site. All survey techniques followed the guidance set out by CIFA (2014, updated 2020), Historic England (2008), and the European Archaeology Council (EAC) (2016).

Bartington Grad 601-2 Traverse Interval 1.0m Sample Interval 0.25m

The only processes performed on data are the following unless specifically stated otherwise:

Zero Mean Traverse	This process sets the background mean of each traverse within each grid to zero. The operation removes instrument striping effects and edge discontinuities over the whole of the data set.
Step Correction (De-stagger)	When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

4 SUMMARY OF RESULTS

- 4.1 A magnetometer survey of approximately three hectares was conducted at Berrow Green Road, Martley and did not produce any results of archaeological interest. The survey identified an *Uncertain* linear trend, possibly related to agricultural processes, as well as plough lines on varying alignments. Large ferrous responses were detected as well as magnetic disturbance.

C. 0.5ha at the north of the site was not suitable for the survey due its use as an allotment.

5 INTRODUCTION

- 5.1 **SUMO Geophysics Ltd** were commissioned to undertake a geophysical survey of an area outlined for development. This survey forms part of an archaeological investigation being undertaken by **Orion Heritage**.

5.2 Site Details

NGR / Postcode	SO 749 595 / WR6 6PQ
Location	The site is located approximately 10km northwest of Worcester. It is bordered to the east by the B4197 and residential properties and to the north by a residential road and allotments. Arable land surrounds the survey area to the west and south.
HER	Worcestershire HER
OASIS Ref. No.	Sumogeop1-518908
District	Malvern Hills District
Parish	Martley Civil Parish
Topography	Generally Flat
Land Use	Agricultural
Geology	Bedrock: Helsby Sandstone Formation – Sandstone
(BGS 2023)	Superficial: None-available
Soils (CU 2023)	Soilscape 6: Freely draining slightly acid loamy soils
Survey Methods	Magnetometer survey (fluxgate gradiometer)
Study Area	c. 3 ha

5.3 **Archaeological Background (HER 2023)**

- 5.3.1 There are 22 archaeological activities and 26 HER monuments recorded within the search area, including the Scheduled Monument of Berrow Hill Iron Age Fort (WSM01272) located approximately c. 840m southwest of the site. The Portable Antiquity Scheme has identified finds within the search area, including medieval and post medieval coins. Archaeological investigations have also recovered artefacts including Roman, post medieval and modern pottery and post medieval clay pipe.

Within the development area there is the potential for medieval and post medieval below ground archaeological features and deposits, given the proximity of recorded earthworks to the east, with further potential for prehistoric and later archaeology relating to the Iron Age hillfort and field system to the south.

5.4 **Aims and Objectives**

- 5.4.1 To locate and characterise any anomalies of possible archaeological interest within the study area.

6 RESULTS

6.1 ***Probable / Possible Archaeology***

6.1.1 No magnetic responses have been recorded that could be interpreted as being of definite archaeological interest.

6.2 ***Uncertain***

6.2.1 A weak linear trend has been detected on an east-west alignment and it has been assigned to the category of *Uncertain*. It generally lacks the defined morphology of anomalies that would usually be interpreted as being of archaeological interest. This anomaly may be the result of agricultural activity but also may be related to the former orchard visible on historic mapping (Fig.05).

6.1 ***Footpath – Corroborated***

6.1.1 A footpath on a northeast-southwest alignment intersects the survey area, and this is visible on both historic mapping and aerial imagery (Fig.05).

6.2 ***Agricultural – Ploughing***

6.2.1 Linear trends, on different alignments, are visible in the data and are a result of modern ploughing effects. Aerial imagery (Fig.05) shows three telegraph poles in the field which explains the different trajectories of the plough lines, as it would be necessary to manoeuvre around the posts.

6.3 ***Ferrous / Magnetic Disturbance***

6.3.1 An area of magnetic disturbance visible in the south of the survey area is likely to have been caused by the removal of an orchard that was previously here, as visible on historic mapping (Fig.05).

6.3.2 Three large ferrous responses, on the line of the path (6.1), result from three telegraph poles in the field; their shadows are visible on aerial imagery (Fig.05).

6.3.3 Ferrous responses close to boundaries are due to adjacent fences and gates. Smaller scale ferrous anomalies ("iron spikes") are present throughout the data and are characteristic of small pieces of ferrous debris (or brick / tile) in the topsoil; they are commonly assigned a modern origin. Only the most prominent of these are highlighted on the interpretation diagram.

7 DATA APPRAISAL & CONFIDENCE ASSESSMENT

7.1 Historic England guidelines (EH 2008) Table 4 states that the typical magnetic response on the local soils / geology is variable. The results from this survey indicate the presence of an *Uncertain* linear trend and ploughing. Consequently, there is no *a priori* reason why archaeological features would not have been detected.

8 CONCLUSION

8.1 The magnetometer survey has not recorded any magnetic responses that could be interpreted as being of definite archaeological interest. An *Uncertain* linear trend is visible, which is likely to be the result of agricultural divisions or the limits of a former orchard. Elsewhere, ploughing has been detected, along with magnetic disturbance from the removed orchard and linear



responses associated with a footpath that crosses the field. Telegraph poles have resulted in strong ferrous responses.

9 REFERENCES




- BGS 2022 British Geological Survey, Geology of Britain viewer [accessed 15/09/2023] *website:* (<http://www.bgs.ac.uk/opengeoscience/home.html?Accordion1=1#maps>)
- ClfA 2014 *Standard and Guidance for Archaeological Geophysical Survey*. Amended 2020. ClfA Guidance note. Chartered Institute for Archaeologists, Reading
Amended 2020 https://www.archaeologists.net/sites/default/files/ClfAS%26GGeophysics_3.pdf
- CU 2022 The Soils Guide. Available: www.landis.org.uk. Cranfield University, UK. [accessed 15/09/2023] *website:* <http://mapapps2.bgs.ac.uk/ukso/home.html>
- EAC 2016 *EAC Guidelines for the Use of Geophysics in Archaeology*, European Archaeological Council, Guidelines 2.
- EH 2008 *Geophysical Survey in Archaeological Field Evaluation*. English Heritage, Swindon (now withdrawn, but used for evaluating suitability of soil types)
- HG 2022 *Heritage Gateway Online Viewer* [accessed 15/09/2023] *website:* <https://www.heritagegateway.org.uk/gateway/>


10 ARCHIVE

- 10.1 The minimally processed data, data images, XY traces and a copy of this report are stored in **SUMO Geophysics Ltd.'s** digital archive, on an internal RAID configured NAS drive in the Midlands Office. These data are also backed up to the Cloud for off-site storage.
- 10.2 The Grey Literature will be archived with OASIS and the relevant HER within a period of 12 months.





Reproduced from Ordnance Survey's 1:25 000 map of 1998 with the permission of the controller of Her Majesty's Stationery Office. Crown Copyright reserved. Licence No: 100018665

	Unsurveyable	
	Survey Areas	



Title:	Site Location	
Client:	Orion Heritage	
Project:	Berrow13639: Green Road, Martley	
Scale:	NOT TO SCALE	Fig No: 01



Title: Magnetometer Survey - Greyscale Plots

Client: Orion Heritage

Project: Berrow13639: Green Road, Martley






Fig No: 02



Title: Magnetometer Survey - Colour Plots

Client: Orion Heritage

Project: Berrow13639: Green Road, Martley











Fig No: 03



KEY

	Uncertain Origin (discrete anomaly / trend)
	Footpath (corroborated)
	Agriculture (plough)
	Magnetic disturbance
	Ferrous






Title: Magnetometer Survey - Interpretation

Client: Orion Heritage

Project: Berrow13639: Green Road, Martley



Scale: 0 metres 75
1: 1500 @ A3

Fig No: 04



KEY

	Uncertain Origin (discrete anomaly / trend)
	Footpath (corroborated)
	Agriculture (plough)
	Magnetic disturbance
	Ferrous




Title: Greyscale Plots, 2009 Aerial Image, c. 1892-1914 Ordnance Survey Map and Interpretation

Client: Orion Heritage

Project: Berrow13639: Green Road, Martley

Scale: NOT TO SCALE Fig No: 05



Title: Minimally Processed Data - Greyscale Plots

Client: Orion Heritage

Project: Berrow13639: Green Road, Martley





Fig No: 06



Title: XY Trace Plots (clipped at +/-15nT)

Client: Orion Heritage

Project: Berrow13639: Green Road, Martley

Scale: 0 metres 50
1:1000 @ A3

Fig No: 07

Standards & Guidance

This report and all fieldwork have been conducted in accordance with the latest guidance documents issued by Historic England (EH 2008) (then English Heritage), the Chartered Institute for Archaeologists (CIfA 2014) and the European Archaeological Council (EAC 2016).

Grid Positioning

For hand held gradiometers the location of the survey grids has been plotted together with the referencing information. Grids were set out using a Trimble R8 Real Time Kinematic (RTK) VRS Now GNSS GPS system.

An RTK GPS (Real-time Kinematic Global Positioning System) can locate a point on the ground to a far greater accuracy than a standard GPS unit. A standard GPS suffers from errors created by satellite orbit errors, clock errors and atmospheric interference, resulting in an accuracy of 5m-10m. An RTK system uses a single base station receiver and a number of mobile units. The base station re-broadcasts the phase of the carrier it measured, and the mobile units compare their own phase measurements with those they received from the base station. This results in an accuracy of around 0.01m.

Technique	Instrument	Traverse Interval	Sample Interval
Magnetometer	Bartington Grad 601-2	1m	0.25m

Instrumentation: **Bartington Grad 601-2**

Bartington instruments operate in a gradiometer configuration which comprises fluxgate sensors mounted vertically, set 1.0m apart. The fluxgate gradiometer suppresses any diurnal or regional effects. The instruments are carried, or cart mounted, with the bottom sensor approximately 0.1-0.3m from the ground surface. At each survey station, the difference in the magnetic field between the two fluxgates is measured in nanoTesla (nT). The sensitivity of the instrument can be adjusted; for most archaeological surveys the most sensitive range (0.1nT) is used. Generally, features up to 1m deep may be detected by this method, though strongly magnetic objects may be visible at greater depths. The Bartington instrument can collect two lines of data per traverse with gradiometer units mounted laterally with a separation of 1.0m. The readings are logged consecutively into the data logger which in turn is daily down-loaded into a portable computer whilst on site. At the end of each site survey, data is transferred to the office for processing and presentation.

Data Processing

Zero Mean	This process sets the background mean of each traverse within each grid to zero.
Traverse	The operation removes striping effects and edge discontinuities over the whole of the data set.
Step Correction (De-stagger)	When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

Display

Greyscale/ Colourscale Plot	This format divides a given range of readings into a set number of classes. Each class is represented by a specific shade of grey, the intensity increasing with value. All values above the given range are allocated the same shade (maximum intensity); similarly, all values below the given range are represented by the minimum intensity shade. Similar plots can be produced in colour, either using a wide range of colours or by selecting two or three colours to represent positive and negative values. The assigned range (plotting levels) can be adjusted to emphasise different anomalies in the data-set.
--------------------------------	---

Presentation of results and interpretation

The presentation of the results includes a 'minimally processed data' and a 'processed data' greyscale plot. Magnetic anomalies are identified, interpreted and plotted onto the 'Interpretation' drawings.

When interpreting the results, several factors are taken into consideration, including the nature of archaeological features being investigated and the local conditions at the site (geology, pedology, topography etc.). Anomalies are categorised by their potential origin. Where responses can be related to other existing evidence, the anomalies will be given specific categories, such as: Abbey Wall or Roman Road. Where the interpretation is based largely on the geophysical data, levels of confidence are implied, for example: Probable, or Possible Archaeology. The former is used for a confident interpretation, based on anomaly definition and/or other corroborative data such as cropmarks. Poor anomaly definition, a lack of clear patterns to the responses and an absence of other supporting data reduces confidence, hence the classification Possible.

Interpretation Categories

In certain circumstances (usually when there is corroborative evidence from desk-based or excavation data) very specific interpretations can be assigned to magnetic anomalies (for example, *Roman Road, Wall, etc.*) and where appropriate, such interpretations will be applied. The list below outlines the generic categories commonly used in the interpretation of the results.

<i>Archaeology / Probable Archaeology</i>	This term is used when the form, nature and pattern of the responses are clearly or very probably archaeological and /or if corroborative evidence is available. These anomalies, whilst considered anthropogenic, could be of any age.
<i>Possible Archaeology</i>	These anomalies exhibit either weak signal strength and / or poor definition, or form incomplete archaeological patterns, thereby reducing the level of confidence in the interpretation. Although the archaeological interpretation is favoured, they may be the result of variable soil depth, plough damage or even aliasing as a result of data collection orientation.
<i>Industrial / Burnt-Fired</i>	Strong magnetic anomalies that, due to their shape and form or the context in which they are found, suggest the presence of kilns, ovens, corn dryers, metal-working areas or hearths. It should be noted that in many instances modern ferrous material can produce similar magnetic anomalies.
<i>Former Field Boundary (probable & possible)</i>	Anomalies that correspond to former boundaries indicated on historic mapping, or which are clearly a continuation of existing land divisions. Possible denotes less confidence where the anomaly may not be shown on historic mapping but nevertheless the anomaly displays all the characteristics of a field boundary.
<i>Ridge & Furrow</i>	Parallel linear anomalies whose broad spacing suggests ridge and furrow cultivation. In some cases, the response may be the result of more recent agricultural activity.
<i>Agriculture (ploughing)</i>	Parallel linear anomalies or trends with a narrower spacing, sometimes aligned with existing boundaries, indicating more recent cultivation regimes.
<i>Land Drain</i>	Weakly magnetic linear anomalies, quite often appearing in series forming parallel and herringbone patterns. Smaller drains may lead and empty into larger diameter pipes, which in turn usually lead to local streams and ponds. These are indicative of clay fired land drains.
<i>Natural</i>	These responses form clear patterns in geographical zones where natural variations are known to produce significant magnetic distortions.
<i>Magnetic Disturbance</i>	Broad zones of strong dipolar anomalies, commonly found in places where modern ferrous or fired materials (e.g. brick rubble) are present.
<i>Service</i>	Magnetically strong anomalies, usually forming linear features are indicative of ferrous pipes/cables. Sometimes other materials (e.g. pvc) or the fill of the trench can cause weaker magnetic responses which can be identified from their uniform linearity.
<i>Ferrous</i>	This type of response is associated with ferrous material and may result from small items in the topsoil, larger buried objects such as pipes, or above ground features such as fence lines or pylons. Ferrous responses are usually regarded as modern. Individual burnt stones, fired bricks or igneous rocks can produce responses similar to ferrous material.
<i>Uncertain Origin</i>	Anomalies which stand out from the background magnetic variation, yet whose form and lack of patterning gives little clue as to their origin. Often the characteristics and distribution of the responses straddle the categories of <i>Possible Archaeology / Natural</i> or (in the case of linear responses) <i>Possible Archaeology / Agriculture</i> ; occasionally they are simply of an unusual form.

Where appropriate some anomalies will be further classified according to their form (positive or negative) and relative strength and coherence (trend: weak and poorly defined).

Appendix B - Technical Information: Magnetic Theory

Detailed magnetic survey can be used to effectively define areas of past human activity by mapping spatial variation and contrast in the magnetic properties of soil, subsoil and bedrock. Although the changes in the magnetic field resulting from differing features in the soil are usually weak, changes as small as 0.1 nanoTeslas (nT) in an overall field strength of 48,000 (nT), can be accurately detected.

Weakly magnetic iron minerals are always present within the soil and areas of enhancement relate to increases in *magnetic susceptibility* and permanently magnetised *thermoremanent* material.

Magnetic susceptibility relates to the induced magnetism of a material when in the presence of a magnetic field. This magnetism can be considered as effectively permanent as it exists within the Earth's magnetic field. Magnetic susceptibility can become enhanced due to burning and complex biological or fermentation processes.

Thermoremanence is a permanent magnetism acquired by iron minerals that, after heating to a specific temperature known as the Curie Point, are effectively demagnetised followed by re-magnetisation by the Earth's magnetic field on cooling. Thermoremanent archaeological features can include hearths and kilns; material such as brick and tile may be magnetised through the same process.

Silting and deliberate infilling of ditches and pits with magnetically enhanced soil creates a relative contrast against the much lower levels of magnetism within the subsoil into which the feature is cut. Systematic mapping of magnetic anomalies will produce linear and discrete areas of enhancement allowing assessment and characterisation of subsurface features. Material such as subsoil and non-magnetic bedrock used to create former earthworks and walls may be mapped as areas of lower enhancement compared to surrounding soils.

Magnetic survey is carried out using a fluxgate gradiometer which is a passive instrument consisting of two sensors mounted vertically 1m apart. The instrument is carried about 30cm above the ground surface and the top sensor measures the Earth's magnetic field whilst the lower sensor measures the same field but is also more affected by any localised buried feature. The difference between the two sensors will relate to the strength of a magnetic field created by this feature, if no field is present the difference will be close to zero as the magnetic field measured by both sensors will be the same.


Factors affecting the magnetic survey may include soil type, local geology, previous human activity and disturbance from modern services.

OASIS Summary for sumogeop1-518908

OASIS ID (UID)	sumogeop1-518908
Project Name	Geophysical Survey, Magnetometry Survey at Berrow Green Road, Martley
Sitename	Berrow Green Road, Martley
Sitecode	13639
Project Identifier(s)	13639
Activity type	Geophysical Survey, Magnetometry Survey, MAGNETOMETRY SURVEY
Planning Id	
Reason For Investigation	Planning requirement
Organisation Responsible for work	SUMO Geophysics Ltd.
Project Dates	01-Sep-2023 - 01-Sep-2023
Location	Berrow Green Road, Martley NGR : SO 74913 58969 LL : 52.22834461654822, -2.368711052206114 12 Fig : 374913,258969
Administrative Areas	Country : England County : Worcestershire District : Malvern Hills Parish : Martley
Project Methodology	<p>Detailed magnetic survey (magnetometry) was chosen as the most efficient and effective method of locating the type of archaeological anomalies which might be expected at this site. All survey techniques followed the guidance set out by CIFA (2014, updated 2020), Historic England (2008), and the European Archaeology Council (EAC) (2016).</p> <p>Bartington Grad 601-2 Traverse Interval 1.0m Sample Interval 0.25m</p> <p>The only processes performed on data are the following unless specifically stated otherwise:</p> <p>Zero Mean Traverse This process sets the background mean of each traverse within each grid to zero. The operation removes instrument striping effects and edge discontinuities over the whole of the data set.</p> <p>Step Correction (De-stagger) When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.</p>

Project Results	A magnetometer survey of approximately three hectares was conducted at Berrow Green Road, Martley and did not produce any results of archaeological interest. The survey identified an Uncertain linear trend, possibly related to agricultural processes, as well as plough lines on varying alignments. Large ferrous responses were detected as well as magnetic disturbance. Unfortunately, around 0.5ha of the site was unsurveyable due to it being used as an allotment.
Keywords	
Funder	Private or public corporation Orion Heritage
HER	Worcestershire HER - unRev - STANDARD
Person Responsible for work	Simon Haddrell
HER Identifiers	
Archives	

Report generated on: 06 Sep 2023, 15:43



- Archaeological
- Geophysical
- Laser Scanning
- Measured Building
- Topographic
- Utility Mapping

SUMO Services Ltd, incorporated under the laws of England and Wales,
Company Registration No.4275993.
Registered Office Unit 8 Hayward Business Centre, New Lane, Havant, Hampshire, PO9 2NL